

DMH metal insulation support anchor



Cross references

Metal insulation stress plate
Cordless hammer drill ABH
Hammer drill SDS plus®
Tool belt

Installation process



Application range

- > For fixing hard insulation materials
- > In combination with the EJOT® DMT metal insulation stress plate also for fixing soft insulation materials
- > For fixing insulation materials for high fire protection requirements

Properties

- > Easy installation by driving in, self-expanding
- > Flammability class A1: non-combustible according to DIN EN 13501-1:2010-01 (test certificate no. PZ 3.1/17-226-1)

Notice

The EJOT® insulation support anchors are used to fasten soft and hard insulating material in rainscreen facades. Insulation boards are fastened according to DIN 18516-1.


Rotary hole drilling is obligatory in aerated concrete and perforated brick masonry.

The DMH-V may only be used subject to dry internal conditions (relative humidity < 70%) and in environments that can be assigned to corrosivity category C1 (insignificant) or C2 (low) according to DIN EN ISO 12944-2:1998-07.

Applications



Technical specifications



Certifications



Characteristic values

Axial distance $a \geq$	120 mm
Edge distance $a_e \geq$	60 mm
Minimum component thickness h_{\min}	80 mm
Recommended tensile loads F_{rec}	
Concrete \geq B25	0.20 kN
Solid sand-lime brick	0.20 kN
Brick	0.20 kN
Vertically perforated brick	0.05 kN
Perforated sand-lime brick	0.05 kN
Recommended transverse loads F_{rec}	
Concrete \geq B25	0.25 kN
Solid sand-lime brick	0.25 kN
Brick	0.25 kN
Vertically perforated brick	0.10 kN
Perforated sand-lime brick	0.15 kN

Product online



Order description	Length L [mm]	Insulation thickness B ≤ [mm]	PU [pieces]	Price/100 [EUR]	Article number	EAN
Alu-zinc steel						
DMH-8x80-V	80	40	250		9800030301	4061245061528
DMH-8x110-V	110	70	250		9800030602	4061245061801
DMH-8x140-V	140	100	250		9800030603	4061245061818
DMH-8x170-V	170	130	250		9800030912	4061245061825
DMH-8x200-V	200	160	250		9800031215	4061245061832
DMH-8x250-V	250	210	200		9800031520	4061245061535
DMH-8x300-V	300	260	200		9800031300	4061245061849

Available in A2 stain-
less steel upon request

